

Wireless Switch Actuator 4-channel, wall-mount

Product ref.: 99082
PRODUCT FEATURES



- Enables switching of low voltage consumers or other relays via radio commands
- 4 independent switching channels
- 4 buttons for direct control on the device
- Direct teaching-in of e.g. wireless push-buttons or remote controls enables comfortable switching of connected loads
- Several remote controls can be connected to one switching channel (even without Homematic Central Control Unit CCU2)
- Relay contact: NO contact (4x) floating
- Low standby power consumption
- Channel LEDs for status display
- Power supply can be provided via external power supply unit (not included in the package contents)
- Maximum ON time can be configured (only in connection with the Homematic Central Control Unit CCU2)

TECHNICAL SPECIFICATIONS

Supply voltage:	7-15 VDC
Current consumption:	26 mA
Power consumption in standby:	0.2 W
Max. switching capacity:	1 A (ohmic load), 42 VDC, 30 VAC
Relay:	4x NO contact
Degree of protection:	IP20
Typ. open area RF range:	300 m
Radio frequency:	868.3 MHz
Dimensions (W x H x D):	89 x 99 x 26 mm
Weight:	81 g

LOGISTIC DATA

Product reference:	99082
EAN code:	4047976990825
Short description:	HM-LC-Sw4-WM
Packing unit:	90
Packaging dimensions:	122 x 112 x 48 mm
Total weight:	152.4 g

PACKAGE CONTENTS

Wireless Switch Actuator 4-channel
 Operating manual in DE and EN